

Verint IP Cameras



CAMERA	V3320 Economic Box	V3320 Economic Mini Dome	V3320 Economic Vandal Dome	V3320 Economic Recess Dome	V4320 WDR Box	V4320 WDR Indoor Mini Dome	V4320 WDR Vandal Dome	V5620PTZ 18X HD PTZ 30X HD PTZ
DESCRIPTION	1080p box camera with high-definition resolution	1080p indoor dome camera with IR illuminator	1080p outdoor weather/vandal dome camera with IR Illuminator	Small in size and price, but heavy on performance 1080p recess mount mini dome	1080p 96+ dB Wide-Dynamic Range box camera	1080p 96+ dB Wide-Dynamic Range indoor dome with auto focus and IR Illuminator	1080p 96+ dB Wide-Dynamic Range IP66 vandal dome with auto-focus and IR illuminator	High-definition 1080p pan-tilt-zoom with 18X zoom or 30X zoom (supports WDR & image stabilization)
ENCLOSURE TYPE	Fixed "box" camera	Fixed surface mount mini dome	IP66 vandal dome	Fixed recess mini dome	Fixed "box" camera	Fixed surface mount mini dome	Fixed surface mount mini dome	PTZ (indoor & outdoor versions)
SENSOR	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.7" CMOS (18X); 1/2.8" CMOS (30X)
RESOLUTION	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel
LENS	C/CS Mount compatible (lens not included)	3-9mm Varifocal	3-9mm Varifocal	2.5mm (-L2) 3.4mm (-L3) 6.0mm (-L6)	C/CS Mount compatible (lens not included)	3-9mm Motorized	3-9mm Motorized	4.7-84.6mm (18X); 4.3-129.0mm (30X)
MAXIMUM PERFORMANCE	1080p @ 30fps	1080p @ 30fps	1080p @ 30fps	1080p @ 30fps	1080p @ 60fps	1080p @ 60fps	1080p @ 60fps	1080p @ 30fps
STREAMING	Triple	Triple	Triple	Dual	Triple	Triple	Triple	Triple
AUDIO	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)
VANDAL/WEATHER RESISTANT	No	No	Yes, IP66	No	No	No	Yes, IP66	Yes, IP66 (outdoor versions)
POWER OVER ETHERNET SUPPORT	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, High PoE+
3-AXIS LENS ROTATION	No	Yes	Yes	No	No	Yes	Yes	N/A
MOUNT TYPE	1/4" x 20 top and bottom Mounts	Surface, Recess, Pendant, Wall	Surface, Recess, Pendant, Wall, Pole	Indoor Recess	1/4" x 20 Top/Bottom	Surface, Recess, Pendant, Wall	Surface, Recess, Pendant, Wall, Pole	Surface, Pendant, Wall, Pole, Recess
ALARM I/Os	Yes 2/2	Yes 2/2	Yes 2/2	No	Yes 2/2	Yes 2/2	Yes 2/2	Yes 2/2



CAMERA	S5120 Box	S5120 Indoor Dome	S5120 Vandal Dome	S5250 Box	S5250 Indoor Dome	S5250 Vandal Dome
DESCRIPTION	1080p H.264 box camera supporting C/CS mount lenses and analytics capability	1080p H.264 indoor dome with auto-focus, 3X remote zoom and analytics capability	1080p H.264 IP66 vandal dome with auto-focus, 3X remote zoom and analytics capability	Ultra-high 5 megapixel H.264 box camera with multi-megapixel rated C/CS mount lens	Ultra-high 5 megapixel H.264 indoor dome with auto-focus and 3X remote zoom	Ultra-high 5 megapixel H.264 IP66 vandal dome with auto-focus and 3X remote zoom
ENCLOSURE TYPE	Fixed "box" camera	Fixed surface mount mini dome	Fixed surface mount vandal/weather mini dome	Fixed "box" camera	Fixed surface mount mini dome	Fixed surface mount vandal/weather mini dome
SENSOR	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.5" CMOS	1/2.5" CMOS	1/2.5" CMOS
RESOLUTION	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel
LENS	C/CS Mount compatible	3-9mm Auto-focus 3X Remote Zoom	3-9mm Auto-focus 3X Remote Zoom	2.8-12mm C/CS Mount Auto-Iris	3-9mm Auto-focus 3X Remote Zoom	3-9mm Auto-focus 3X Remote Zoom
MAXIMUM PERFORMANCE	1080p @ 30fps	1080p @ 30fps	1080p @ 30fps	5 MP @ 7fps	5 MP @ 7fps	5 MP @ 7fps
STREAMING	Triple	Triple	Triple	Triple	Triple	Triple
AUDIO	Yes	Yes	Yes	Yes	Yes	Yes
VANDAL/WEATHER RESISTANT	No	No	Yes	No	No	Yes
POWER OVER ETHERNET SUPPORT	Yes	Yes	Yes	Yes	Yes	Yes
3-AXIS LENS ROTATION	N/A	Yes	Yes	N/A	Yes	Yes
MOUNT TYPE	1/4" x 20 top and bottom mounts	Surface, Pendant, Wall, Recess	Surface, Pendant, Wall, Pole, Recess	1/4" x 20 top and bottom mounts	Surface, Pendant, Wall, Recess	Surface, Pendant, Wall, Pole, Recess
ALARM I/Os	Yes	Yes	Yes	Yes	Yes	Yes

World-Class Service and Support

At Verint, we are dedicated to the success of our partners and customers. To this end, we've developed world-class customer support programs and service offerings. Staffed by Verint experts in all facets of networked video deployment and use, Verint's Customer Support Program features live technical support, web-based resources, advanced replacements and a host of on-site professional services.

Verint. Powering Actionable Intelligence®

Verint® Systems Inc. (NASDAQ: VRNT) is a global leader in Actionable Intelligence® solutions for customer engagement optimization, security intelligence, and fraud, risk and compliance. Today, more than 10,000 organizations in over 180 countries use Verint solutions to improve enterprise performance and make the world a safer place. Learn more at www.verint.com.

Americas

✉ info@verint.com

☎ 1-800-4VERINT

Europe, Middle East & Africa

✉ marketing.emea@verint.com

☎ +44(0) 1932 839500

Asia Pacific

✉ marketing.apac@verint.com

☎ +(852) 2797 5678

verint.com

twitter.com/verint

facebook.com/verint

blog.verint.com

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change. Not all functionality is available in all configurations. Please contact Verint for current product features and specifications. All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners. © 2015 Verint Systems Inc. All Rights Reserved Worldwide. 05.2015