

Verint IP Cameras



| CAMERA | V3420 RD | V3620-HS-POE | V3720 FDW | V3720 BTW |
|-----------------------------|---|--|--|--|
| FORM FACTOR | Recess Mini Dome | Heightstrip | Fixed Dome | Bullet Network Camera |
| DESCRIPTION | 1080p Recess mount mini dome | 1080p Surface mount Heightstrip camera with 180° lens | 1080P WDR Dome with remote focus & zoom IR Illuminator | 1080P WDR Bullet with remote focus & zoom IR Illuminator |
| ENCLOSURE TYPE | Fixed recess mini dome | Fixed Heightstrip | Fixed surface mount | IP66 Bullet Camera |
| SENSOR | 1/2.7" CMOS | 1/2.9" Progressive CMOS | 1/2.9" Progressive CMOS | 1/2.9" Progressive CMOS |
| RESOLUTION | 1080p, 2 Megapixel | 1080p, 2 Megapixel | 1080P, 2 Megapixel | 1080P, 2 Megapixel |
| LENS | Fixed 2.8mm | Fixed-facial | Motorized Varifocal 2.8 ~12 mm | Motorized Varifocal 2.8 ~12 mm |
| MAX PERFORMANCE | 1080p @ 30fps | 1080p @ 30fps | 1080p @ 30fps | 31080p @ 30fps |
| STREAMING | 3 Streams | 4 streams | 3 streams | 3 streams |
| AUDIO | Internal Microphone | No | Internal microphone | No |
| VANDAL/ WEATHER RESISTANT | No | No | IP66, IK10 | IP66, IK10 |
| POWER OVER ETHERNET SUPPORT | 802.3af, Class 2 | IEE 802.3af PoE Class 1 | IEEE 802.3af PoE Class 0 | IEEE 802.3af PoE Class 0 |
| 3-AXIS LENS ROTATION | No | No | Yes | No |
| MOUNT TYPE | Recessed Mount | Surface Mount | Surface, Recess, Pendant, Wall, Pole, Corner | Surface mount bullet |
| ALARM I/Os | No | No | No | No |
| OPERATING TEMPERATURE | Starting Temperature: 0°C ~ 45°C (32°F ~ 113°F) Working Temperature: -10°C ~ 45°C (14°F ~ 113°F) | Starting Temperature: 0°C ~ 40°C (32°F ~ 104°F) Working Temperature: 10°C ~ 40°C (14°F ~ 104°F) | Starting Temperature: -10°C ~ 60°C (14°F ~ 140°F) Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F) | Starting Temperature: -10°C ~ 60°C (14°F ~ 140°F) Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F) |
| POWER CONSUMPTION | 3.3w | Max. 2.01 W | Max. 12.95 W (IR on) / Max. 9 W (IR off) | Max. 12.95 W (IR on) / Max. 9 W (IR off) |
| ONBOARD STORAGE | Micro SDHC/SDXC | No | Micro SDHC/SDXC | Micro SDHC/SDXC |
| WDR TECHNOLOGY | True WDR | WDR Enhanced | True WDR | True WDR |
| ONVIF PROFILE S | Yes | Yes | Yes | Yes |
| OTHER TECHNOLOGY | AdaptiveStream | Adaptivestream | WDR, Adaptivestream, Smart IR, motorized focus and zoom | WDR, Adaptivestream, Smart IR, motorized focus and zoom |
| CODEC | H.264 & MJPEG | H.264 | H.265, H.264 | H.265, H.264 |
| IR ILLUMINATOR | No | No | Effective up to 30 meters | Effective up to 30 meters |
| DIMENSIONS | Ø 60x115mm | 27.7 (D) x 49.3 (W) x 866.4 (H) mm | Ø 133.7 x 103.8 mm | 85 x 85 x 214.5 mm |
| ANALOG OUT | No | No | No | No |
| DYNAMIC RANGE | 100dB | 50.6 dB | 120 dB | 120 dB |
| INDUSTRY COMPLIANCE | NDAA Compliant | NDAA Compliant | NDAA Compliant | NDAA Compliant |

Verint IP Cameras



| CAMERA | 4420-M-P/W | 4750 FDW-DN | 4750BX-DN | 8080BX-DN | 8080FDW-DN |
|------------------------------------|--|--|---|--|---|
| FORM FACTOR | Discreet, Modular Camera | Network Dome | Box camera | IP box | Outdoor IP dome |
| DESCRIPTION | 2MP Modular Camera with Video Core, Camera module & Five Meter Cable | 5MP WDR network dome with remote focus & zoom / IR Illuminator | 5MP WDR network box camera | 8MP(4K) 120dB WDR Box Camera | 8MP (4K) 120dB WDR Dome with remote focus & zoom / IR Illuminator |
| ENCLOSURE TYPE | Discreet Mount | Fixed Dome | Fixed Box Camera | Fixed Box Camera | Fixed Surface mount |
| SENSOR | 1/2.7" CMOS | 1/2.8" | 1/2.8" | 1/2.5" | 1/2.5" |
| RESOLUTION | 1080p, 2 Megapixel | 5MP, 2592x1944 | 5MP, 2592x1944 | 4K, 3840x2160 | 4K, 3840x2160 |
| LENS | 90 Degree Pinhole or 180 Degree Fisheye | f2.7~13.5mm, F1.4~2.8, Motorized | CS Mount (Lens not included) | CS mount (Lens not included) | f3.4-9mm, F1.5, Motorized |
| MAX PERFORMANCE | 1080p 30fps | 5MP@30fps | 2592x1944 @ 30fps | Dual Stream: 8MP @ 15fps & 1080p @ 15fps | Dual Stream: 8MP @ 15fps & 1080p @ 15fps |
| STREAMING | 4 Streams | 3 streams | 3 streams | 3 streams | 3 streams |
| AUDIO | In/Out (G711, G726) | In/Out (G711) | In/Out (G711) | Internal Microphone In/Out (G.711) | In/Out (G.711) |
| VANDAL/ WEATHER RESISTANT | No | IK10/IP67 | No | No | IP67, IK10 |
| POWER OVER ETHERNET SUPPORT | IEEE 802.3af, Class 2 | IEEE 802.3af, Class 3 | IEEE 802.3af, Class 3 | IEEE 802.3af(PoE), class 3 compliant | IEEE 802.3af(PoE), class 4 compliant |
| 3-AXIS LENS ROTATION | No | Yes | No | No | Yes |
| MOUNT TYPE | Discreet Recessed, Flush, Corner, gangbox, ATM & more. | Surface, Recess, Pendant, Wall, Pole, Corner | ¼" Threaded Top/Bottom | ¼" Threaded Top/Bottom | Surface, Recess, Pendant, Wall, Pole, Corner |
| ALARM I/Os | Yes | Yes | Yes | Yes | Yes |
| OPERATING TEMPERATURE | -10°C ~ 50°C (14°F ~ 122°F) | -40°C ~ 60°C (-40°F ~ 140°F) | -10°C ~ 55°C (14°F ~ 131°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -40°C ~ 50°C (-40°F ~ 122°F) |
| POWER CONSUMPTION | 5.5w | 13.5W (Max) | 13.5W (Max) | 7.5W (Max) | 25W (Max) |
| ONBOARD STORAGE | Micro SDHC/SDXC | Micro SDHC/SDXC | Micro SDHC/SDXC | Micro SDHC/SDXC | Micro SDHC/SDXC |
| WDR TECHNOLOGY | True WDR | True WDR, 120dB | True WDR | True WDR | True WDR |
| ONVIF PROFILES | Yes | Yes | Yes | Yes | Yes |
| OTHER TECHNOLOGY | WDR, Adaptivestream | Adaptive IR, Motorized Focus & Zoom, WDR, Analytics | Remote Back Focus, WDR, Analytics | Remote Back Focus, WDR, Analytics | Pliris, Adaptive IR, motorized Focus & zoom, WDR, Analytics |
| CODEC | H.264 & MJPEG | H.265/HEVC Main Profile H.264 Main/High/Baseline Profile | Smart Compression: iZone, iStream, Dynamic 3DNR | H.264 | H.264 |
| IR ILLUMINATOR | No | Effective up to 40 meters | No | No | Effective up to 40 meters |
| DIMENSIONS | Camera unit: (Without cable) Pinhole: Ø 24 x 37mm Wide: Ø 24 x 43mm Video Core:105 x 84 x 30mm | Ø 135mmx125mm | 73x104x62mm | 72x145x62mm | Ø 147x140mm |
| ANALOG OUT | No | No | No | Yes | Yes |
| DYNAMIC RANGE | 100dB | 120dB | 120dB | 120dB | 120dB |
| INDUSTRY COMPLIANCE | NDAA Compliant | NDAA Compliant | NDAA Compliant | NDAA Compliant | NDAA Compliant |

The Customer Engagement Company™

Americas

info@verint.com

1-800-4VERINT

Europe, Middle East & Africa

info.emea@verint.com

+44(0) 1932 839500

Asia Pacific

info.apac@verint.com

+(852) 2797 5678



verint.com



twitter.com/verint



facebook.com/verint



blog.verint.com

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change. Not all functionality is available in all configurations. Please contact Verint for current product features and specifications. All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners. © 2020 Verint Systems Inc. All Rights Reserved Worldwide. VFSS0072.210126

VERINT®