

# Verint Network Video Recorder Line Card



	FEATURE	ADVANTAGE	BENEFIT
<b>CAPTURE</b>	Video Capture	Network video recorders capture high-quality video images from analog, IP, and megapixel cameras. It's new feature includes HD-over-coax to help streamline high-definition video over coaxial cable.	Provides organizations a more complete view of events and operations and a more efficient, time-saving approach to security and operational efficiency. It also allows organizations to protect their investment by using current analog infrastructures and easily adding IP cameras for additional coverage. The video quality adds more accuracy when investigating cases and the lower bit rate helps save on storage.
<b>MONITOR</b>	Verint EdgeVMS Op-Center™	Centrally configure, manage, and monitor the functioning of Verint EdgeVR's enterprise wide.	Allows managers, security staff, and system administrators to monitor, manage, and troubleshoot their Verint NVRs from a central location.
<b>ANALYZE</b>	Verint Analytics	Advanced platform to capture video and data, provide immediate video viewing, and help analyze information to expedite investigations.	Enhances the efficiency and effectiveness of security operations with powerful fraud investigation tools including video and teller/ATM transactions, face detection and more.
<b>EASE OF USE</b>	Industry-leading System Interfaces and Verint Video Investigator™ Provides Unified Video Viewing	Devices easily interface with security, banking and retail. A unified video viewing application helps users search video by time, date, transaction, or event.	Provides a more complete understanding of the context in which events occur and enable organizations to tailor recording according to the information these systems provide. Day-at-a-glance, week-at-a-glance, and motion-based searches help users quickly pinpoint video of interest. Users can easily view or export 1-16 cameras for faster investigations.
<b>SERVICE &amp; SUPPORT</b>	Easily Access Parts	With RAID, easily replaced hard drives, and an easy to replace fan and power supply, Verint EdgeVR's provide a long-term value.	Flexible options to remove and replace product parts provides lower service and maintenance fees. This option is great for organizations that need to manage hundreds or thousands of NVRs through a typical security product life cycle.
<b>RELIABLE</b>	Embedded Operating System and Design	Verint EdgeVR's include an embedded operating system, and system components, designed to support the security market.	The embedded system design provides superior component availability and reliability, and the embedded operating system allows for superior security and system up-time. This can significantly lower maintenance costs, as well as improve the total cost of ownership.

# Verint NVR Line Card



	EdgeVR 40	EdgeVR 60	EdgeVR 80	EdgeVR 150	EdgeVR 300
<b>VIDEO</b>					
Video Input	4 cameras	8 cameras	12 cameras	16 cameras	64 cameras
Onboard Analog/IP Inputs	4 analog / 4 IP (4 port POE option)	8 IP (8 Port POE)	8 analog / 4 IP (4 port POE option)	16 analog / 8 IP	16 analog / 64 IP
Video Compression	H.264				
Maximum Recording Rate	120fps (NTSC) / 100fps (PAL)	240fps at 1080P	240fps (NTSC) / 200fps (PAL)	480fps (NTSC) / 400fps (PAL)	1920fps (NTSC) / 1600fps (PAL)
Resolution	CIF/2CIF/4CIF/1MP/2MP/3MP/5MP	1MP/2MP/3MP/5MP/8MP/12MP	CIF/2CIF/4CIF/1MP/2MP/3MP/5MP	CIF/2CIF/4CIF/1MP/2MP/3MP/5MP	CIF/2CIF/4CIF/1MP/2MP/3MP/5MP and 8 optional HD CVI
<b>STORAGE</b>					
Storage Space	1TB to 4TB	2TB to 5TB	1TB to 4TB	2TB to 4TB	Up to 60TB
Hard Drive Options	1 or 2 non-removable drives (2.5 in)	1 or 2 non-removable drives	1 or 2 non-removable drives	1 or 2 non-removable drives	Up to 6 removable drives
RAID Options	RAID 1				RAID 1, 5 & 6
<b>INTERFACES</b>					
Local Monitor Outputs	#1 VGA or DVI or Composite	2 x HDMI for Local Monitor, 2 USB 3.0 & 3 USB 2.0	#1 VGA or DVI or Composite	#1 VGA or DVI or Composite	#1 is VGA / #2 is DVI or composite using optional splitter
Network	Dual ethernet 10/100/1000 Base-T models + 4 POE Option	RJ45 Ports - 12 ports, 8 x POE+ and two NON-POE ports, LAN 1 & 2 and POE Ports - 8 x POE+ with support up to max of 120W with built in integrated port management through the NVR Interface	Dual ethernet 10/100/1000 Base-T models + 4 POE Option	Dual ethernet 10/100/1000 Base-T models	Dual ethernet 10/100/1000 Base-T
Data Integration	ATM, POS, Teller, Alarm Systems, Access Control	ATM, POS, Teller, Alarm systems and support for SR-8 data interface device	ATM, POS, Teller, Alarm Systems, Access Control	ATM, POS, Teller, Alarm Systems, Access Control	ATM, POS, Teller, Alarm Systems, Access Control
Alarm Inputs	4 programmable contacts (NO or NC)	4 programmable contacts (Normally Open or Normally Closed) and 4 relay contacts	8 programmable contacts (NO or NC)	8 programmable inputs and one relay output using optional hardware	4 programmable inputs and one relay output
<b>SOFTWARE</b>					
Investigation Software	Verint Video Investigator	Verint Video Investigator	Verint Video Investigator	Verint Video Investigator	Verint Video Investigator
Monitoring Software	Verint EdgeVMS Op-Center				
<b>ANALYTICS</b>					
Surveillance Analytics	Yes, via external encoder	Up to 2 channels	Yes, via external encoder	Yes, via external encoder	Up to 16 channels onboard
Face Detection	N/A	Up to 2 channels	N/A	N/A	Up to 16 channels onboard
<b>GENERAL</b>					
Security	Key locked HDD bays; all network ports closed; SSL communication with IP devices	All network ports closed; SSL communication with IP devices	Key locked HDD bays; all network ports closed; SSL communication with IP devices	All network ports closed; SSL communication with IP devices	Key locked front panel; all network ports closed; SSL communication with IP devices
Industry Compliance	NDAA Compliant				
Firmware	Embedded Linux OS in Flash memory				
<b>PHYSICAL</b>					
Enclosure	Metal chassis with wall mount bracket	Metal chassis with wall mount bracket	Metal chassis with wall mount bracket	Metal chassis with wall mount bracket	3U Metal chassis; rack mountable
Dimensions	8.1" x 10.2" x 2.3" (20.5cm x 26cm x 6cm)	9.5/8 x 8.5/8 x 11.3/16, 24.5cm x 22cm x 4.5cm	8.1" x 10.2" x 2.3" (20.5cm x 26cm x 6cm)	15" x 14" x 3.5" (38cm x 35.5cm x 9 cm)	15in x 17.5in x 5.25in (38cm x 43cm x 13cm)

## World-Class Service and Support

At Verint, we are dedicated to the success of our partners and customers. To this end, we've developed world-class customer support programs and service offerings. Staffed by Verint experts in all facets of networked video deployment and use, Verint's Customer Support Program features live technical support, web-based resources, advanced replacements and a host of on-site professional services.

## The Customer Engagement Company™

### Americas

info@verint.com

1-800-4VERINT

### Europe, Middle East & Africa

info.emea@verint.com

+44(0) 1932 839500

### Asia Pacific

info.apac@verint.com

+ (852) 2797 5678



verint.com



twitter.com/verint



facebook.com/verint



blog.verint.com

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change. Not all functionality is available in all configurations. Please contact Verint for current product features and specifications. All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners. © 2020 Verint Systems Inc. All Rights Reserved Worldwide. VFSS0052.201102

# VERINT®