

Verint S2201e-R-HD Decoder

The Verint® S2201e-R-HD Decoder incorporates advanced H.264 decompression technology to deliver superior video quality for up to 16 HD (1080p) video tiles to an HDMI monitor making it useful in a variety of environments.

Designed to be able to display up to sixteen HD (1080p) tiles on a high-definition HDMI LCD or plasma monitor. The S2201e-R-HD Decoder is a great choice for a remote monitor solution. It provides excellent video quality, high reliability and easy installation in a lightweight and compact design.

Advanced Video Technology with Lowest TCO

Verint is at the forefront of networked video technology, with over two decades of experience providing security intelligence solutions to government and industry worldwide. Using custom Dell hardware to power our software, the S2201e-R-HD Decoder is a versatile edge device built on the latest video technology, integrated with the industry's broadest video portfolio and built for easy installation and operation. Designed to enhance any video network, this decoder will help organizations realize the benefits of displaying HD IP video.



Key Features:

- HDMI OR Display Port
- Displays up to 16 tiles at 1080p
- Enables organizations to realize the benefits of HD IP video
- Compatible with Verint EdgeVMS
- Compact, energy efficient, and environmentally friendly
- Web interface for easy implementation and configuration
- VESA mount included

Verint S2201e-R-HD Decoder

VIDEO

Outputs/Connectors	HDMI & Display Port out. (only one can be used at a time)
Performance	16 x 1080p, 200FPS across the unit
Resolution	From CIF to 1080P (higher resolutions possible)
Compression	H.264 (MPEG-4 Part 10/AVC) Main Profile
Tiles	Max of 16 tiles on 1 monitor • Display options of 1x1, 2x2, 2x3, 3,3, 4x4
Video Latency	115msec

NETWORK

Interface	10/100/1000M Gigabit Ethernet
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, RTSP, or multicast IP • Others: DNS, NTP, SNMP v1/v2c/v3 (MIB-II), HTTP, HTTPS, DHCP client, 802.1x
Security	SSL-based authentication, password protected, HTTPS

SERIAL PORTS

Optional	USB to serial interface using the FTDI transceiver
Operating Mode	Transparent serial port supporting any asynchronous serial protocol

AUDIO

Audio	Input: -46 to -3 dBV into 30 Kohms (line-in)
Connectors	1/8 in. (3.5 mm) stereo jacks

MANAGEMENT

Configuration and Firmware Upgrade	Supported in Verint EdgeVMS, SConfigurator and Web browser interface (single device firmware upgrade)
------------------------------------	---

ELECTRICAL

Supply/Voltage	100-240v
Power Consumption	Max. 65W

PHYSICAL

Dimensions	7.0L x 1.4W x 7.2H in. (17.8L x 3.6W x 18.2H cm)
Weight	2.6 lbs. (1.18 kg)
Operating Temperature	5° to 35° C (41° to 95° F)
Humidity	20% to 80% (non-condensing)
Firmware	Embedded Linux-based operating system
Accessories	Vesa Mount Included. Dimensions: 6.75L x 2.5W x 7.5H in. (17L x 6W x 19H cm)

* Features listed in this document are subject to change. Not all functionality is available in all configurations

World-Class Service and Support

At Verint, we are dedicated to the success of our partners and customers. To this end, we've developed world-class customer support programs and service offerings. Staffed by Verint experts in all facets of networked video deployment and use, Verint's Customer Support Program features live technical support, web-based resources, advanced replacements and a host of on-site professional services.

The Customer Engagement Company™

Americas

info@verint.com
1-800-4VERINT

Europe, Middle East & Africa

info.emea@verint.com
+44(0) 1932 839500

Asia Pacific

info.apac@verint.com
+(852) 2797 5678

	verint.com
	twitter.com/verint
	facebook.com/verint
	blog.verint.com

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change. Not all functionality is available in all configurations. Please contact Verint for current product features and specifications. All marks referenced herein with the © or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners. © 2017 Verint Systems Inc. All Rights Reserved Worldwide. V1237.180726

VERINT®